

# WESTERN CABLE CORPORATION

888-805-0355 RIVERSIDE CALIFORNIA

## EXPANDABLE POLYESTER BRAIDED SLEEVING

<b>Operating temp range:</b>	-70C to +125C	<b>UL recognized</b>
<b>Specific gravity:</b>	1.31	<b>CSA Listed</b>
<b>Tensile strength:</b>	100,000 psi	<b>Mil-I-631 (Fungus testing)</b>
<b>Elongation</b>	20%	
<b>Melt Temperature</b>	250C	
<b>Low temp Flexibility</b>	-70C	

Part No.	Size Inches	Size Range Inches	Flat Width Range	Wall Thickness	Put Ups	
					4Ft Sticks	Spools
XS100-1/8	.125	3/32 - 1/8	-	0.025	NA	500
XS100-1/4	.250	1/8 - 3/8	1/4 - 3/8	0.025	NA	500
XS100-1/2	.500	1/4 - 3/4	1/2 - 3/4	0.025	NA	500
XS100-3/4	.750	1/2 - 1-1/4	3/4 - 1-1/8	0.025	NA	500
XS100-11/4	1.250	3/4 - 1-1/2	1-1/8 - 1-5/8	0.025	NA	250
XS100-13/4	1.750	1-1/4 - 2-1/2	1-3/4 - 2-1/8	0.025	NA	250
XS100-2	2.000	1-1/2 - 3	2 - 2-7/8	0.025	NA	250
XS100-21/2	2.500	1-3/4 - 3-1/2	2-1/2 - 3-1/2	0.025	NA	100

Stock Color: Black and Natural



Sales@Western-Cable.com 951-683-8777, Fax:951-683-8778

# WESTERN CABLE CORPORATION

888-805-0355 RIVERSIDE CALIFORNIA

## EXPANDABLE FLAME-RETARDANT POLYESTER BRAIDED SLEEVING

<b>Operating temp range:</b>	-70C to +125C	<b>UL VW-1 recognized</b>
<b>Specific gravity:</b>	1.31	<b>CSA Listed</b>
<b>Tensile strength:</b>	50,000 psi	<b>Mil-I-631 (Fungus testing)</b>
<b>Elongation</b>	25%	
<b>Melt Temperature</b>	240C	
<b>Low temp Flexibility</b>	-70C	

Part No.	Size Inches	Size Range Inches	Flat Width Range	Wall Thickness	Put Ups	
					4Ft Sticks	Spools
XS100FR-1/8	.125	3/32 - 1/8	-	0.025	NA	500
XS100FR-1/4	.250	1/8 - 3/8	1/4 - 3/8	0.025	NA	500
XS100FR-1/2	.500	1/4 - 3/4	1/2 - 3/4	0.025	NA	500
XS100FR-3/4	.750	1/2 - 1-1/4	3/4 - 1-1/8	0.025	NA	500
XS100FR-11/4	1.250	3/4 - 1-1/2	1-1/8 - 1-5/8	0.025	NA	250
XS100FR-13/4	1.750	1-1/4 - 2-1/2	1-3/4 - 2-1/8	0.025	NA	250
XS100FR-2	2.000	1-1/2 - 3	2 - 2-7/8	0.025	NA	250
XS100FR-21/2	2.500	1-3/4 - 3-1/2	2-1/2 - 3-1/2	0.025	NA	100

Stock Color: Black with White Tracer, White with Black Tracer



Sales@Western-Cable.com 951-683-8777, Fax:951-683-8778