

# WESTERN CABLE CORPORATION

888-805-0355 RIVERSIDE CALIFORNIA

## EXTRUDED PTFE (TEFLON) TUBING - STANDARD WALL

Continuous service temp:	250C	UL 224 VW-1
Dielectric Strength	600 V/mil	CSA OFT
UL rating:	600V @ 200C	Mil-I-22129
Tensile Strength:	2,500 psi (Min)	ASTM-3653
		ASTM-3295

### STANDARD WALL

Ordered as AWG Size	Expanded I.D. Min (Inches)	Nominal Wall	Put Ups		Note
TS250-24	0.022	0.012	100	1000	
TS250-22	0.027	0.012	100	1000	
TS250-20	0.034	0.016	100	1000	
TS250-19	0.038	0.016	100	1000	
TS250-18	0.042	0.016	100	1000	
TS250-17	0.047	0.016	100	1000	
TS250-16	0.053	0.016	100	1000	
TS250-15	0.059	0.016	100	1000	
TS250-14	0.066	0.016	100	500	
TS250-13	0.076	0.016	100	500	
TS250-12	0.085	0.016	100	500	
TS250-11	0.095	0.016	100	500	
TS250-10	0.106	0.016	100	500	
TS250-9	0.118	0.020	100	500	
TS250-8	0.133	0.020	100	NA	
TS250-7	0.148	0.020	100	NA	
TS250-6	0.166	0.020	100	NA	
TS250-5	0.186	0.020	100	NA	
TS250-4	0.208	0.020	100	NA	
TS250-3	0.234	0.020	100	NA	
TS250-2	0.263	0.020	100	NA	
TS250-1	0.294	0.020	100	NA	
TS250-0	0.330	0.020	100	NA	



Sales@Western-Cable.com 951-683-8777, Fax:951-683-8778

# WESTERN CABLE CORPORATION

888-805-0355 RIVERSIDE CALIFORNIA

## EXTRUDED PTFE (TEFLON) TUBING - THIN WALL

Continuous service temp:	250C	UL 224 VW-1
Dielectric Strength	600 V/mil	CSA OFT
UL rating:	300V @ 200C	AMS-3655
Tensile Strength:	2,500 psi (Min)	ASTM 3295 TYPE 1 CL B

### THIN WALL

Ordered as AWG Size	Nominal I.D.	Nominal Wall	Put Ups		Notes
TT250-30	0.012	0.009	100	1000	
TT250-28	0.015	0.009	100	1000	
TT250-26	0.018	0.010	100	1000	
TT250-24	0.022	0.010	100	1000	
TT250-22	0.027	0.012	100	1000	
TT250-20	0.034	0.012	100	1000	
TT250-19	0.038	0.012	100	1000	
TT250-18	0.042	0.012	100	1000	
TT250-17	0.047	0.012	100	1000	
TT250-16	0.053	0.012	100	1000	
TT250-15	0.059	0.012	100	1000	
TT250-14	0.066	0.012	100	500	
TT250-13	0.076	0.012	100	500	
TT250-12	0.085	0.012	100	500	
TT250-11	0.095	0.012	100	500	
TT250-10	0.106	0.012	100	500	
TT250-9	0.118	0.015	100	500	
TT250-8	0.133	0.015	100	NA	
TT250-7	0.148	0.015	100	NA	
TT250-6	0.166	0.015	100	NA	
TT250-5	0.186	0.015	100	NA	
TT250-4	0.208	0.015	100	NA	
TT250-3	0.234	0.015	100	NA	
TT250-2	0.263	0.015	100	NA	
TT250-1	0.294	0.015	100	NA	
TT250-0	0.330	0.015	100	NA	



Sales@Western-Cable.com 951-683-8777, Fax:951-683-8778

# WESTERN CABLE CORPORATION

888-805-0355 RIVERSIDE CALIFORNIA

## EXTRUDED PTFE (TEFLON) TUBING - LIGHT WALL

Continuous service temp:	250C	UL 224 VW-1
Dielectric Strength	600 V/mil	CSA OFT
UL rating:	150V @ 200C	AMS-3654
Tensile Strength:	2,500 psi (Min)	ASTM 3295 TYPE 1 CL A

### LIGHT WALL

Ordered as AWG Size	Nominal I.D.	Nominal Wall	Put Ups		Notes
ETT250-30	0.012	0.006	100	1000	
ETT250-30	0.015	0.006	100	1000	
ETT250-26	0.018	0.006	100	1000	
ETT250-24	0.022	0.006	100	1000	
ETT250-22	0.027	0.006	100	1000	
ETT250-20	0.034	0.006	100	1000	
ETT250-19	0.038	0.006	100	1000	
ETT250-18	0.042	0.006	100	1000	
ETT250-17	0.047	0.006	100	1000	
ETT250-16	0.053	0.006	100	1000	
ETT250-15	0.059	0.006	100	1000	
ETT250-14	0.066	0.008	100	500	
ETT250-13	0.076	0.008	100	500	
ETT250-12	0.085	0.008	100	500	
ETT250-11	0.095	0.008	100	500	
ETT250-10	0.106	0.008	100	500	
ETT250-9	0.118	0.008	100	NA	
ETT250-8	0.133	0.008	100	NA	
ETT250-7	0.148	0.008	100	NA	
ETT250-6	0.166	0.010	100	NA	
ETT250-5	0.186	0.010	100	NA	
ETT250-4	0.208	0.010	100	NA	
ETT250-3	0.234	0.010	100	NA	
ETT250-2	0.263	0.010	100	NA	
ETT250-1	0.294	0.010	100	NA	
ETT250-0	0.330	0.012	100	NA	



Sales@Western-Cable.com 951-683-8777, Fax:951-683-8778